







From whimsical to realistic, Cre8Play's artists use textures and colors to create fun sculptures for children to explore. Constructed of durable Glass Fiber Reinforced Concrete, (GFRC), our unique designs allow for climbing and stepping to inspire the imagination.




L: 17' 6"
W: 18' 6"
H: 4' 6"
4,500 LBS





If you determine that less than 12" of surfacing is required, make sure the top of the concrete slab is 12" below the top of the protective surfacing.



NOTE: Read installation instructions thoroughly before starting installation process.

Step 1: Lay out the area and prepare the site for install. Concrete must be installed over a solid, level base. Check local soil condition and codes. See product installation instructions for minimum use zone requirements to ensure proper spacing and adequate surfacing area.

Step 2: Pour a concrete slab for the component. Refer to the typical concrete slab section in this document. The concrete should be flush with the ground level. Allow time for the concrete to completely cure before continuing.

Step 3: Refer to the typical in-ground footing detail on excavating the holes for the component.

Step 4: Using an appropriate lull-type forklift or boom, place the posts into the footing holes and components on the concrete slab. Unfurl net climber and be sure that the net fits taut between the posts before final mounting. See the the mounting detail below for information on how to attach the net to the posts. Plumb the posts keeping the net taut. Temporarily brace the posts.

Step 5: Pour your concrete per footing detail. Allow time for the concrete to completely cure before removing temporary bracing. See the hardware recommendation for information on anchoring equipment down to your concrete slab. Refer to the surfacing manufacturer for installation of an approved impact attenuating play surface around the component with a minimum use zone in every direction.


Included Items:

Item	Description	Quantity
Octopus Climber	Play Equipment	11
Spiderweb Net	Play Equipment	1
Anchor Bolt 5/8" x 4"	Mounting Hardware	18
D-shackle, Bushing and Spacers	Mounting Hardware	6 sets


Anchor Bolt Installation:

Anchor Bolt Size	ANSI Standard Drill Bit Diameter	Anchor Head (Socket Size)	Minimum Embedment	Hole Depth
1/2" x 3"	7/16"	3/4"	2 1/2"	3 1/2"
5/8" x 4"	1/2"	13/16"	3 1/2"	4 1/2"
5/8" x 6"	1/2"	13/16"	5 1/2"	6 1/2"


Step 1: Drill



Step 2: Anchor



NOTE: Always wear eye protection appropriate to the task at hand.




**Mounting Detail
Exploded View**
(Not to Scale)


**Mounting Detail
Assembled View**
(Not to Scale)

NOTES PRIOR TO CONSTRUCTION:


- Use appropriate equipment to lift and move the play equipment.
- Check local codes and requirements prior



Mounting Detail
(Not to Scale)



Mounting Detail
(Not to Scale)




Typical Component Footing Detail
Check local soil conditions.
(Not to Scale)

! WARNING

INSTALLATION OVER A HARD SURFACE SUCH AS CONCRETE, ASPHALT, OR PACKED EARTH MAY RESULT IN SERIOUS INJURY OR DEATH FROM FALLS.

THE REMOVAL OF HELMETS, HOODS, DRAWSTRINGS, AND ACCESSORIES AROUND THE NECK IS RECOMMENDED TO PREVENT ENTANGLEMENT AND STRANGULATION.

PLAY EQUIPMENT AND/OR SURFACING MAY BE HOT.



TYPICAL 6" CONCRETE SLAB DETAIL (NOT TO SCALE)
CHECK LOCAL SOIL CONDITIONS.

NOTE: Always wear eye protection appropriate to the task at hand.